



# D8229 Access Keypad



- ▶ **PIN keypad**
- ▶ **Easy installation**
- ▶ **Two LED indicators**
- ▶ **Sturdy enclosure**

The D8229 Access Keypad sends output in a Wiegand 26-bit format. Enter a personal identification number (PIN) to obtain access. There are keys for numbers 0 through 9, for the number symbol (#), and for the asterisk symbol (\*). Each time you press a key, one of the light emitting diode (LED) indicators emits a red light and an annunciator emits a beep.

## Functions

### Easy Installation

The D8229 Access Keypad installs easily in a US standard single-gang switch box. For outdoor applications, use a suitable weather-resistant back box.

### Two LED Indicators

The D8229 Access Keypad has two light emitting diode (LED) indicators. One LED emits green light to indicate access granted. The second LED emits red light to indicate the door is locked. The second LED also emits red light when a key is pressed.

### Sturdy Enclosure

The D8229 Access Keypad has a steel enclosure. The electronic components are embedded in protective material. These properties make the D8229 Access Keypad resistant to damage from moisture, harsh weather, and vandalism.

## Certifications and Approvals

Region	Certification
USA	UL ALVY: Access Control Systems Units (UL294), UEHX7: Signaling Appliances, Miscellaneous Certified for Canada (cUL)

## Installation/Configuration Notes

### Compatibility Information

Reader	D8229 Access Keypad
Systems	ReadykeyPRO Readykey Readykey KeyPAC D9412G Control Panel D7412G Control Panel

### Connection Considerations

When using 1.2 mm (18 AWG) cable, you can place the reader up to 152 m (500 ft) away from the door controller.

## Technical Specifications

### Environmental

Relative Humidity	0% to 100%, non-condensing For UL Listed applications, 0% to 85%, non-condensing
Temperature (Operating)	-40°C to +71°C (-40°F to +160°F) For UL 294 applications, -30°C to +60°C (-22°F to +140°F)

### Electrical

Current (Input)	20 mA idle; 120 mA peak
Voltage (Input)	5 ±1 VDC or 12 ±3 VDC; jumper selectable
Indicators	1 red LED and 1 green LED

### Mechanical

Dimensions	13 cm x 8 cm x 1 cm (5 in. x 3 in. x 0.4 in.)
Weight	0.6804 kg (1.5 lb)
Keypad	12 keys
Material	Stainless steel

## Ordering Information

### D8229 Access Keypad

### D8229

Access keypad in sturdy, steel enclosure; electronic components sealed in protective material

**Americas:**  
Bosch Security Systems, Inc.  
130 Perinton Parkway  
Fairport, New York, 14450, USA  
Phone: +1 800 289 0096  
Fax: +1 585 223 9180  
security.sales@us.bosch.com  
www.boschsecurity.us

**Europe, Middle East, Africa:**  
Bosch Security Systems B.V.  
P.O. Box 80002  
5600 JB Eindhoven, The Netherlands  
Phone: +31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

**Asia-Pacific:**  
Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6258 5511  
Fax: +65 6571 2698  
apr.securitysystems@bosch.com  
www.boschsecurity.com

### Represented by